

Overview

HPE Ethernet 10/25Gb 2-port 640FLR-SFP28 Adapter

The HPE Ethernet 10/25Gb 2-port 640FLR-SFP28 adapter for ProLiant Gen9 rack servers provides full-featured, high performance, converged 25Gb Ethernet that accelerates IT services and increases data center efficiency across a broad range of I/O intensive enterprise, cloud and Telco workloads.

It offers a rich set of offload technologies including overlay network tunneling and storage as well as RDMA over Converged Ethernet (RoCE) capabilities that increase host efficiency and virtualization performance.

The HPE Ethernet 640FLR-SFP28 can provide up to 100Gbps of converged bi-directional Ethernet bandwidth, helping to alleviate network bottlenecks. This adapter can also run at 10 Gb for customers who have not changed the infrastructure/switches to 25 Gb yet.



HPE Ethernet 10/25Gb 2-port 640FLR-SFP28Adapter

Models

HPE Ethernet 10/25Gb 2-port 640FLR-SFP28 Adapter

817749-B21

Overview

Kit Contents

- HPE Ethernet 10/25Gb 2-port 640FLR-SFP28Adapter
- Quick install card
- Product warranty statement

Compatibility

HPE ProLiant Server Support

- HPE ProLiant DL380 Gen9
- HPE ProLiant DL360 Gen9
- HPE ProLiant DL180 Gen9
- HPE ProLiant DL160 Gen9
- HPE ProLiant DL120 Gen9
- HPE ProLiant DL60 Gen9
- HPE ProLiant DL80 Gen9
- HPE ProLiant DL560 Gen9
- HPE ProLiant DL580 Gen9
- Apollo 2000 Gen9
- Apollo 4200 Gen9
- Apollo 4530 Gen9
- Apollo 6000 XL230a/XL250a Gen9

Switches

- Arista 7060CX-32S 100G
- Juniper QFX1002-36Q
- HPE FlexFabric 5950 32QSFP28 Switch
- HPE FlexFabric 5950 25G
- Juniper QFX5200
- Cisco 3232C
- HP Altoline 25G

Standard Features

Product Features

- Dual 25Gb ports provide up to 100Gb bi-directional per adapter
- Converges RoCE with LAN traffic on a single 25 GbE wire
- Tunnel Offload support for VXLAN and NVGRE
- RDMA over Converged Ethernet (RoCE) for greater server efficiency and lower latency
- Supports UEFI and legacy boot options
- Industry-leading throughput and latency performance
- Over eight million small packets/s, ideal for web/mobile applications, mobile messaging, and social media
- FlexibleLOM Adapter
- Greater bandwidth with PCIe 3.0
- Jumbo Frames support
- Active Health Systems support
- Support for Preboot eXecution Environment (PXE)
- Supports receive-side scaling (RSS) for the efficient distribution of network receive processing across multiple CPUs in multiprocessor systems
- Support for Windows SMB Direct
- Supports VMWare NetQueue, Microsoft Virtual Machine Queue (VMQ) for Windows
- Supports SR-IOV
- Support WOL

Dual-port 25 Gigabit Ethernet Throughput (theoretical bandwidth) The 25 Gbps bi-directional Ethernet transfer rate per port (100 Gbps aggregate bi-directional), providing the network performance needed to improve response times and alleviate bottlenecks. 25Gb Ethernet bandwidth is ideal for high performance computing, database clusters.

PCI Express Interface The HPE 640FLR-SFP28 is designed with an eight lane (x8) PCI Express bus based on the PCIe 3.0 standard. The adapter is backward compatible with four lane (x4) PCI Express, automatically auto-sensing between x8 and x4 slots.

Jumbo Frames The HPE 640FLR-SFP28 adapter supports Jumbo Frames, permitting up to a 9,600 byte (KB) transmission unit (MTU) when running Ethernet I/O traffic. This is over 5X the size of a standard 1500-byte Ethernet frame. With Jumbo Frames, networks can achieve higher throughput performance and lower CPU utilization. These attributes are particularly useful for storage, database transfer and tape backup operations.

MSI-X Message Signaled Interrupt (Extended) provides performance benefits for multi-core servers by load balancing interrupts between CPUs/cores.

TCP/UDP/IP For overall improved system response, the HPE 640FLR-SFP28 adapter supports standard TCP/UDP/IP offloading techniques including:

- TCP/IP checksum offload (TCO) moves the TCP and IP checksum offloading from the CPU to the network adapter.

Standard Features

- Large Send Offload (LSO) or TCP Segmentation Offload (TSO) allows the TCP segmentation to be handled by the adapter rather than the CPU.

RoCE (RoCEv2)

RoCE is an accelerated I/O delivery mechanism that allows data to be transferred directly from the user memory of the source server to the user memory of the destination server bypassing the operating system (OS) kernel. Because the RDMA data transfer is performed by the DMA engine on the adapter's network processor, the CPU is not used for the data movement, freeing it to perform other tasks such as hosting more virtual workloads (increased VM density). RDMA also bypasses the host's TCP/IP stack, in favor of upper layer InfiniBand protocols implemented in the adapter's network processor. The bypass of the TCP/IP stack and the removal of a data copy step reduce overall latency to deliver accelerated performance for applications such as Microsoft Hyper-V Live Migration, Microsoft SQL and Microsoft SharePoint with SMB Direct.

Tunnel Offload

Minimize the impact of overlay networking on host performance with tunnel offload support for VXLAN and NVGRE. By offloading packet processing to adapters, customers can use overlay networking to increase VM migration flexibility and virtualized overlay networks with minimal impact to performance. HPE Tunnel Offloading increases I/O throughput, reduces CPU utilization, and lowers power consumption. Tunnel Offload supports VMware's VXLAN and Microsoft's NVGRE solutions.

Interrupt Coalescing

Interrupt coalescing (interrupt moderation) groups multiple packets, thereby reducing the number of interrupts sent to the host. This process optimizes host efficiency, leaving the CPU available for other duties.

802.1p QoS Tagging

IEEE quality of service (QoS) 802.1p tagging allows the adapter to mark or tag frames with a priority level across a QoS-aware network for improved traffic flow.

802.1Q VLANs

IEEE 802.1Q virtual local area network (VLAN) protocol allows each physical port of the HPE 640FLR-SFP28 adapter to be separated into multiple virtual NICs for added network segmentation and enhanced security and performance. VLANs increase security by isolating traffic between users. Limiting the broadcast traffic to within the same VLAN domain also improves performance.

Network Management

Management Support

Like all HPE ProLiant server adapters, the HPE 640FLR-SFP28 adapter ships with agents that can be managed from HPE Systems Insight Manager or other management application that support SNMP.

Server Integration

The HPE 640FLR-SFP28 adapter is a validated, tested, and qualified solution that is optimized for HPE ProLiant servers. Hewlett Packard Enterprise validates a wide variety of major operating systems drivers with the full suite of web-based enterprise management utilities including HPE Intelligent Provisioning and HPE Systems Insight Manager that simplify network management.

This approach provides a more robust and reliable networking solution than offerings from other vendors and provides users with a single point of contact for both their servers and their network adapters.

Standard Features

Configuration Utilities Each HPE 640FLR-SFP28 ships with a suite of operating system-tailored configuration utilities that allow the user to enable initial diagnostics and configure adapter teaming. This includes a patented teaming GUI for Microsoft Windows operating systems. Additionally, support for scripted installations of teams in a Microsoft Windows environment allow for unattended OS installations.

LED Indicators Bracket LED indicators show link integrity and network activity for easy troubleshooting.

Preboot eXecution Environment (PXE) Support for PXE enables automatic deployment of computing resources remotely from anywhere. It allows a new or existing server to boot over the network and download software, including the operating system, from a management/ deployment server at another location on the network. Additionally, PXE enables decentralized software distribution and remote troubleshooting and repairs.

Warranty

- Maximum: The remaining warranty of the HPE product in which it is installed (to a maximum three-year, limited warranty).
- Minimum: One year limited warranty.

NOTE: Additional information regarding worldwide limited warranty and technical support is available at: <http://h17007.www1.hp.com/us/en/enterprise/servers/warranty/index.aspx#.V4e3tPkrJhE>

Service and Support

Service and Support HPE Technology Services

HPE Technology Services offers you consultants and support experts to solve your most complex infrastructure problems. We help keep your business running, boost availability and avoid downtime.

Protect your business beyond warranty with HPE Care Pack Services

When you buy HPE Options, it's also a good time to think about what level of service you may need. HPE Care Pack services provide total care and support expertise with committed response choices designed to meet your IT and business need.

HPE Foundation Care services deliver scalable support-packages for Hewlett Packard Enterprise industry-standard servers and software. You can choose the type and level of service that is most suitable for your business needs. New to this portfolio is HPE Collaborative Support. If you are running business critical environments, Hewlett Packard Enterprise offers Proactive Care or Critical Advantage. These services help you deliver high levels of application availability through proactive service management and advanced technical response.

Here is the support service recommendation from the Foundation Care and Proactive Care portfolio. For customized support service solution, Hewlett Packard Enterprise can work with you to tailor a service solution for your unique support requirements using broader services portfolio of Foundation Care and Proactive Care.

Recommended Services

Recommended HPE Care Pack Services for optimal satisfaction with your HPE product 3-Year HPE 24x7 4 hour Response, Hardware Support Onsite Service

Provides you with rapid remote support and if required an Hewlett Packard Enterprise Authorized representative who will arrive on site any time and day of the year to begin hardware maintenance service within 4 hours of the service request being logged.

<http://h20566.www2.hp.com/portal/site/hpsc?ac.admitted=1467740454177.125225703.1938120508>

OR

3-Year HPE 24x7 4 hour Response, HPE Collaborative Support

Offers customers a single point of contact for server problem diagnosis, hardware problem resolution, and basic software problem diagnosis, fault isolation, and resolution if available to Hewlett Packard Enterprise. If the problem is with HPE HW, the representative will arrive on site any time and day of the year to begin hardware maintenance service within 4 hours of the service request being logged. In case, the issue is with Hewlett Packard Enterprise or supported third-party software product and cannot be resolved by applying known fixes, Hewlett Packard Enterprise will contact the third-party vendor and create a problem incident on your behalf.

HPE ProLiant Server Hardware Installation

Provides for the basic hardware installation of Hewlett Packard Enterprise branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner.

<https://www.hp.com/h20195/v2/GetDocument.aspx?docname=5981-9356EN>

Related Services

Related HPE Care Pack Services to enhance your HPE product experience

Service and Support

3-Year HPE 24x7 4 hour Response, Proactive Care or Critical Advantage

Helps optimize your systems and delivers high levels of application availability through proactive service management and advanced technical response. A skilled Technical Manager will own your query or issue end to end until resolved, delivering a single point of contact for you.

<http://h20566.www2.hp.com/portal/site/hpsc?ac.admitted=1467740454177.125225703.1>

OR

3-Year HPE 6-hour Onsite Call-to-Repair, HPE Collaborative Support

Offers customers a single point of contact for server problem diagnosis, hardware problem resolution to return the hardware in operating condition within 6 hours of the initial service request to the HPE Global Solution Center, and basic software problem diagnosis, fault isolation, and resolution if available to Hewlett Packard Enterprise. In case, the issue is with Hewlett Packard Enterprise or supported third-party software product and cannot be resolved by applying known fixes, Hewlett Packard Enterprise will contact the third-party vendor and create a problem incident on your behalf.

HPE Proactive Select Service

Provides a flexible way to purchase Hewlett Packard Enterprise best-in-class consultancy and technical services. You can buy Proactive Select Service Credits when you purchase your hardware and then use the credits over the next 12 months.

<https://www.hp.com/h20195/v2/GetDocument.aspx?docname=4AA3-8855ENW&search=4AA3-8855ENW>

Insight Remote Support

Provides 24 X 7 remote monitoring, proactive notifications, and problem resolution. Learn more

<http://h20564.www2.hp.com/hpsc/doc/public/display?docId=c04844073>

HPE Support Center Personalized online support portal with access to information, tools and experts to support Hewlett Packard Enterprise business products. Submit support cases online, chat with Hewlett Packard Enterprise experts, access support resources or collaborate with peers. Learn more <https://www.hp.com/us/en/support.html>

The HPE Support Center Mobile App allows you to resolve issues yourself or quickly connect to an agent for live support. Now, you can get access to personalized IT support anywhere, anytime.

HPE Insight Remote Support and HPE Support Center are available at no additional cost with a Hewlett Packard Enterprise warranty, HPE Care Pack or Hewlett Packard Enterprise contractual support agreement.

NOTE:NOTE:NOTE: The Hewlett Packard Enterprise Support Center Mobile App is subject to local availability.

Parts and materials Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements. Supplies and consumable parts will not be provided as part of this service; standard warranty terms and conditions apply. Parts and components that have exceeded their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual or the technical product data sheet will not be provided, repaired or replaced as part of this service.

Service and Support

Warranty / Service Coverage For ProLiant servers and storage systems, this service covers HPE-branded hardware options qualified for the server, purchased at the same time or afterward, internal to the enclosure, as well as external monitors up to 22" and tower UPS products; these items will be covered at the same service level and for the same coverage period as the server unless the maximum supported lifetime and/or the maximum usage limitation has been exceeded. Coverage of the UPS battery is not included; standard warranty terms and conditions apply.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Hewlett Packard Enterprise due to malfunction. It does not apply to any exchange of Disk or SSD/Flash Drives that have not failed. SSD/Flash Drives that are specified by Hewlett Packard Enterprise as consumable parts and/or that have exceeded maximum supported lifetime and/or the maximum usage limit as set forth in the manufacturer's operating manual or the technical data sheet are not eligible for the defective media retention service feature option.

For more information

To learn more on services for HPE ESSN Options, please contact your Hewlett Packard Enterprise sales representative or Hewlett Packard Enterprise Authorized Channel Partner. Or visit:

<https://www.hpe.com/us/en/servers.html>

Additional Options

Cables	HPE 25 GbE SFP28 to SFP28 0.5m Direct Attach Copper Cable	844471-B21
	HPE 25 GbE SFP28 to SFP28 1m Direct Attach Copper Cable	844474-B21
	HPE 25 GbE SFP28 to SFP28 3m Direct Attach Copper Cable	844477-B21
	HPE 25 GbE SFP28 to SFP28 5m Direct Attach Copper Cable	844480-B21
	HP X242 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	J9283B
	HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable	J9285B
	HP B-series SFP+ to SFP+ Active Copper 1.0m Direct Attach Cable	AP818A
	HP B-series SFP+ to SFP+ Active Copper 3.0m Direct Attach Cable	AP819A
	HP B-series SFP+ to SFP+ Active Copper 5.0m Direct Attach Cable	AP820A
	HP BladeSystem c-Class Small Form-Factor Pluggable 1m 10GbE Copper Cable	487652-B21
	HP BladeSystem c-Class Small Form-Factor Pluggable 5m 10GbE Copper Cable	537963-B21
	HPE X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable	JD095C
	HPE X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable	JD096C
	HPE X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097C
	HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper	JD097B
	HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable	JD095B
	HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable	JD096B

Transceivers	HPE 25Gb SFP28 SR Transceiver (100m)	845398-B21
	HP BladeSystem c-Class 10Gb SFP+ SR Transceiver	455883-B21
	HP BladeSystem c-Class 10Gb SFP+ LR Transceiver	455886-B21
	X132 10G SFP+ LC SR Transceiver	J9150A
	HP X132 10G SFP+ LC LRM Transceiver	J9152A

Fiber Optic Cables	HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable	AJ833A
	HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable	AJ834A
	HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
	HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
	HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
	HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A

NOTE:NOTE:NOTE: Fiber transceivers and cables must be purchased separately for fiber-optic environments.

Technical Specifications

General Specifications	Network processor	Mellanox ConnectX-4 Lx	
	Data rate	Two ports, each at 50 Gbps bi-directional; 100 Gbps aggregate bi-directional theoretical bandwidth.	
	Bus type	PCI Express v3.0 (Gen 3) x8	
	Form factor	FlexibleLOM	
	IEEE Compliance	802.3ae, 802.1Q, 802.3x, 802.1p, 802.3ad/LACP, 802.1AB(LLDP), 802.1Qbg, 802.1Qbb, 802.1Qaz, 802.3az, 802.3AS, 802.1Qau, IEEE 1588v2	
	Connector	Two SFP28 (SR, DAC)	
Power and Environmental Specifications	Operating	Temperature	5° to 60° C (41° to 140° F)
		Humidity	8% to 90% relative humidity
	Non-operating	Temperature	-40°C to 70°C / -40°F to 158°F
		Humidity	Minimum to be the higher (more moisture) of -12°C (10.4°F) dew point or 8% relative humidity. Maximum to be the lower (less moisture) of 24°C (75.2°F) dew point or 90% relative humidity. non-condensing.
	Power requirement	10.5 W typical, 14 W maximum	
	Other	PCIe 3.0 RoHS compliance 6 of 6 IPv4, IPv6 CE Microsoft WHQL (Windows Hardware Quality Labs)	
Operating System Support	Windows:	Microsoft Windows Server 2012, 2012 R2 Microsoft Windows Hyper-V 2012 R2 Windows WSSC v. Next	
	Linux:	Red Hat Enterprise Linux 6.6,6.7, 7.0,7.1, 7.2 SUSE Linux Enterprise Server 11 SUSE Linux Enterprise Server 12 Ubuntu 14.04.2,12.04.5	
	HyperVisors:	Citrix XenServer 6.5 (Creedence),Augusta Vmware ESXi 5.5U3, 6.0U1 NOTE:NOTE:NOTE: Supported when running 10Gb only Vmware ESXi 6.0U2 NOTE:NOTE:NOTE: Support 10Gb and 25Gb	

Additional Options

Oracle Solaris:

Solaris 11.1

For more operating system support & certification information, please visit:

http://h17007.www1.hpe.com/us/en/enterprise/servers/supportmatrix/redhat_linux.aspx#.V4e8tPkrJD8

Environment-friendly Products and Approach**End-of-life Management and Recycling**

Hewlett Packard Enterprise offers end-of-life Hewlett Packard Enterprise product return, trade-in, and recycling programs in many geographic areas. For trade-in information, please go to: <http://www.hpe.com/info/recycle> To recycle your product, please go to: <http://www.hpe.com/info/recycle> or contact your nearest Hewlett Packard Enterprise sales office. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard Enterprise web site at: <http://www.hpe.com/info/recycle>. These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment.

Summary of Changes

Date	Version History	Action	Description of Change
22-Jul-2016	From Version 1 to 2	Changed	QuickSpecs sections were updated.
06-Jun-2016	Version 1	Created	New QuickSpecs.



Sign up for updates

© Copyright 2016 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Windows is a US registered trademark of Microsoft Corporation.

c04815215 - 15526 - Worldwide - V2 - 22-July-2016

